

Millersburg Area Volunteer Fire Fighters Association

Bump and Run Rules

Adopted, January 27, 2008

We must all remember we are here to be SAFE and have a day to race for FUN. Any American or foreign made front engine car can enter the race. Any driver may enter any number of vehicles under that drivers name, but if a driver has two cars called for me same heat, that driver can only run one vehicle and the other cars are disqualified for that heat. A driver may enter as many cars as they choose, but will only receive one pass, NOT one pass per car entered. The owner must perform the following steps in preparing the car.

1. NO FOUR WHEEL DRIVE VEHICLES.
2. All glass must be removed from the car, including the headlights and taillights. No glass in doors, trunk, or interior. Wire mesh is allowed.
3. All decorative trim and chrome must be removed.
4. Every vehicle must have a solidly mounted seat belt.
5. Cars must have forward and reverse gears and operational brakes before the heat starts.
6. All doors must fasten shut with wire, chains or welded straps.
7. Hood and deck lid must be wired or chained. The hood and the trunk deck must have a twelve inch (12" fire suppression hole. Two (2) chains minimum on the hood. The trunk may be welded.
8. Radiator must be stock and in stock location, no auxiliary radiators. NO ANTI-FREEZE ALLOWED. You will be checked.
9. Battery must be moved to a safe position in car and securely fastened. Covered with a fire proof material. Batteries must have fall top.
10. The original gas tank must be removed from the original location, and moved to the back seat area. Must be wrapped or covered with fire proof material and securely fastened. Should be no more than five (5) gallons.
11. A fall width rear mud flap is MANDATORY on rear wheel drive cars. Front wheel drive cars are optional. No snowmobile tracks, tarps, cardboard or wood allowed. Rubber flaps only
12. D O.T Approved tires. 33" maximum height No liquid filled, double or dual tires, foam filled Absolutely no reworking or reinforcing of rims. No studs or screws in tires. Rims must be stock. Agricultural tires allowed.

13. Roll bar recommended, but not required. Roof support roll over bar is required in the interior of car. A vertical post fastened securely to floor and roof. Six point maximum inside car. May extend through the firewall or trunk wall. Driver door reinforcing is allowed and recommended. Accidental driver's door hits are possible. Remember this is a bump and run NOT a demolition derby.

14. Radiator support allowed but may not exceed in front of the radiator. No pipes or bars in front of the radiator.

15. A 3" maximum circumference pipe, angle/channel iron may replace a stock bumper. In stock bumper location only. Bumper will not exceed the width of the car. No rub rails.

16. Entrants are encouraged to decorate their cars in good taste. No profanity please. Profanity will be covered, this is a family day.

17. Small sign mounted on the roof of car approximately 12Mx24" for the number of the car.

18. Track officials may disqualify a car that may not be safe at any time.

19. No creeping. If a red flag is out and you are caught moving you will be disqualified This will be strictly enforced.

20. Electric fuel pumps must have shut off switch on dash. This is for track official safety.

21. Must be a licensed driver and of legal age. Anyone under 18 must have parental signature for waiver.

MILLERSBURG BUMP AND RUN RULES
FOR PICK-UP TRUCKS

1. Fuel tank mounted in front center of box. NO stock tanks. Steel tanks or neoprene construction in fire-proof material.
2. Weld front box between box edge and cab on each side with metal plate 1/4" thick.
3. Battery must be in a safe location. Must have fall lid top.
4. Stock truck boxes only.
5. A maximum pipe, angle/channel iron may replace a stock bumper in the stock bumper location only. Bumper will not exceed width of truck. No rub rails.
6. Stock wheel and tires. No modification of either,
7. Tail gates not required but must have chain across to keep original width. If tailgates are used, they must be welded, chained or strapped.
8. Tires 33" maximum. Agg tires are allowed.
9. No creeping. If a red flag is out and you are caught moving, you will be disqualified. This is for track official safety.

Print Driver Name: _____

Sign Driver Name: _____

Address: _____
